

# Eiffel Trans HD series

Heavy Duty Transmission and Drivetrain Oils



## Product Data Sheet

---

### Product Description

Eiffel Trans HD series is a range of extra high performance transmission and drive train oils, formulated with high quality base stocks and advanced additive system to meet or exceed the requirements of Caterpillar TO-4 specification. Suitable to provide heavy duty performance benefits in powershift transmissions, gearboxes, final drives and high pressure hydraulic applications. It helps in maximizing the productivity in construction, quarrying and mining equipment operating under severe conditions.

### Features & Benefits

- Balanced static and dynamic friction coefficients, helps in optimizing clutch friction retention and control of slippage. Thus ensuring increased load carrying capacity & improvement in clutch life.
- Good compatibility with various clutch materials and elastomers.
- Excellent foam control property enhances performance of wet brakes by controlling brake chattering.
- Outstanding oxidation & thermal stability reduces high pressure hydraulic pump wear and minimizes sludge build keeping the application clean.
- Outstanding anti-wear protection & load carrying capabilities, helps in reducing wear and extends the life of gearboxes, final drives and transmissions.

### Specifications

Eiffel Trans HD series meets or exceeds following International and Builder specifications:

- Caterpillar TO-4
- Allison C-4
- Vickers M-2950-S

### Application

- Suitable for use in heavy duty transmissions, gear boxes, final drives and hydraulic systems used in off-highway applications.
- Off-highway applications including: mining, agriculture, construction and quarrying.
- Suitable for certain manual, powershift and automatic transmissions where Allison C-4 fluids (SAE 10W & 30 grades) are recommended.
- Hydraulic applications in most of mobile equipment.

### Typical Characteristics

| Eiffel Trans HD    | Test Method | Units | 10W   | 30    | 50    | 60    |
|--------------------|-------------|-------|-------|-------|-------|-------|
| Density @ 15 °C    | ASTM D 4052 | gm/cc | 0.880 | 0.892 | 0.904 | 0.910 |
| Viscosity @ 100 °C | ASTM D 445  | cSt   | 5.6   | 11.6  | 20.5  | 25.6  |
| Viscosity @ 40 °C  | ASTM D 445  | cSt   | 35    | 108   | 254   | 356   |
| Viscosity Index    | ASTM D 2270 | -     | 96    | 95    | 95    | 95    |
| Pour Point         | ASTM D 97   | °C    | -33   | -18   | -12   | -12   |
| Flash Point (COC)  | ASTM D 92   | °C    | 214   | 230   | 242   | 242   |

*The above figures are typical of blends with normal production tolerance and do not constitute a specification.*