

Eiffel Duramax Silver 4AT 20W-50 SL/CF JASO MB

Multigrade Gasoline and Diesel Engine Oil



Product Data Sheet

Product Description

Eiffel Presti Silver 4AT 20W50 SL (JASO MB) is designed with high quality Synthetic Blend base stocks and advanced technology additive system to provide high level of protection and performance. It works harder than other conventional motor oils by continuously preventing dirt and sludge build-up and reduces engine noise. This product meets the requirements of most scooter manufacturers, with naturally aspirated or turbo charged engines, operating in all round seasons and adapted to vehicles equipped with catalytic converters running on unleaded fuels. It is suitable for modern 4-stroke Scooters of European, Taiwanese, Japanese, Chinese, Indian manufacturers.

Features & Benefits

- Superior protection against viscosity and thermal breakdown.
- Excellent detergency and dispersancy.
- Superior sludge protection for greater engine reliability.
- Enhanced wear protection and improved engine cleanliness.

Specifications

Eiffel Duramax Silver meets or exceeds following International and Builder specifications:

- API 4AT SL, SL, SJ, CF
- ACEA A3/B3

Application

Eiffel Duramax Silver is suitable for use in following:

Modern 4-stroke Scooter engines.

Naturally aspirated or turbo-charged engines.

Typical Characteristics

Eiffel Duramax Silver	Test Method	Units	20W-50
Density @ 15 °C	ASTM D 4052	gm/cc	0.890
Viscosity @ 100 °C	ASTM D 445	cSt	20.1
Viscosity @ 40 °C	ASTM D 445	cSt	176
Viscosity Index	ASTM D 2270	-	125
Pour Point	ASTM D 97	°C	-24
Flash Point (COC)	ASTM D 92	°C	236
Total Base Number	ASTM D 2896	mg KOH/g	7.8
Phosphorous	ASTM D 4951	% wt	0.098
CCS Viscosity	ASTM D 5293	cP	7560 @ -15 °C

The above figures are typical of blends with normal production tolerance and do not constitute a specification.

For further information, please contact: sales@eiffellubricants.com